


ULBRICH SPECIALTY WIRE PRODUCTS

692 Plant Road Westminster, SC 29693 (864) 647-6087 info@ulbrich.com

CAPABILITY SHEET

High Performance RF Cable Materials



You have cable-making challenges. We have **engineered wire solutions**.

Leading Supplier to the Microwave and RF Cable industry, Ulbrich is your source for a broad range of precision wires for your specialty cable requirements. Ulbrich's quality, technology and know-how will drive your performance higher.

- Consistent Performance
- Reduced VSWR Spikes
- Improved Flex Life
- High Aspect Ratio
- Higher Strength
- Lighter Weight





- 4-Axis FFT Analysis and Reporting
- Precision Drawing and Annealing
- In-Line Statistical Process Controls
 Ensure High Cpk & Ppk Values
- Customized Mechanical Properties Enable Wrap Optimization and Variability Control
- In-House Silver Plating
- Special Alloys Available on Request
- ISO 9001:2008, ASTM B298 Compliant

CENTER CONDUCTOR WIRE

Bare and Silver Plated Copper **MATERIALS**

Silver Plated Copper Clad Aluminum

Silver Plated Copper Clad Steel

DIAMETERS 0.002" to 0.294" (44 AWG to 1 AWG)

> 0.008" to 0.294" (32 AWG to 1 AWG) 0.004" to 0.040" (38 AWG to 18 AWG)

12" Flange (D-50), 8" Flange (D-25), 5" Flange (D-5), **COMMON SPOOLS**

22" Reel, Other Sizes to Meet Customer Needs

HELICAL WRAP WIRE

ASPECT RATIOS Up to 375:1

Thickness: 0.0005" (0.0127mm) – 0.004" (0.1mm) SIZE RANGES AVAILABLE

> 0.020" (0.5mm) - 0.325" (8.255mm) Width:

Bare Copper and Silver Plated Copper (CD102, CD110) **MATERIALS AVAILABLE**

> **PACKAGING** Available in Biconical or Straight Flanged Spools

BRAID WIRE

SIZE RANGES AVAILABLE Thickness: 0.0015" (0.0381mm) – 0.004" (0.1mm)

> Width: 0.020" (0.5mm) – 0.150" (3.8mm)

MATERIALS AVAILABLE Silver Plated Copper, Tin Plated Copper,

Bare Copper, Copper Alloys

